Kodak PIXPRO

Digital Cameras

SP1 ACTION CAM



FEATURES:

Finally a go anywhere 1080p video camera that can keep up with your non-stop life. Rugged, compact and ultra versatile the KODAK PIXPRO SP1 Digital Action Cam easily mounts to helmets, boards, handle bars and just about anything else you can imagine. From everyday life to white knuckle adventures, we've got you covered. And with built-in wireless connectivity, sharing with your inner circle or the world couldn't be easier. KODAK PIXPRO Digital Cameras - Tell your story.

- 32ft. / 10m Waterproof
- 6.5ft. / 2m Shockproof
- Dustproof, Freezeproof
- Full HD 1080p Video
- 14MP CMOS
- 10 fps Burst Shooting
- 1.5" LCD
- Wireless Connection



Available Colors:





























Digital Camcorder

SPECIFICATIONS SP	SPEC	ECIFICA	TIONS	SP1
-------------------	------	---------	-------	-----

Effective Image Sensor Pixels

Total Image Sensor Pixels

Lens

Focal Length

[35mm film equivalent]

F number Lens Construction Optical 700m Focusing Range

Field of View (FOV) Anti-Handshake

Number of Recording Pixels

Still Image Movie

Image Compression

File Format Still Image

Movie

Shooting Modes Auto

Detection Features Waterproof

Shockproof Up to 6.5 ft. / 2m Dustproof

Freezeproof Yes Wireless

LCD Display ISO Sensitivity

AF Method Exposure Metering Method

Exposure Control Method Burst Mode

Playback Modes

White Balance Control

Recording Media

Other Features

Jacks

Weight

Power Shooting Capability

(Battery Performance) Operation Environment

Dimensions (WxHxD)

Supplied Accessories

14.24 Megapixels

15.31 Megapixels [1/2.3" CMOS]

3.0 mm [16.8 mm] F28

6 groups 6 elements Fixed Focus, 160 Degree Normal: 60 cm − ∞

Ultra Wide, Medium, Narrow, Water Ring

Electronic Image Stabilization

(4:3) 14MP: 4320x3240, 5MP: 2592x1944, (16:9) 10MP: 4320x2432

1920x1080 (30fps), 1280x960 (50fps), 1280x960 (30fps), 1280x720 (60fps), 1280x720 (30fps), 848x480 (60fps)

High-Speed Movie: 848x480 (120fps)

Best

Exif 2.3 (JPEG)

Movie Format: MOV (H.264), Audio: Linear PCM (Stereo)

Face Up to 32 ft. / 10m

Equivalent to JIS/IEC (IP6X) 14°F / -10°C

1.5 inch (115K Pixels) Auto (100 - 800)

Single

Single AF, Multi-AF (TTL 9-point), Face Detection Artificial Intelligence AE (AiAE), Face AE

Program AE (AE-Lock Available) Approx. 10fps (Full Resolution)

Auto (AWB), Daylight, Cloudy, Flourescent, Underwater

Internal Memory: Approx. 100MB

Micro SD/Micro SDHC Card (Up to 32GB Support) [MMC Card not supported]

Multi-Language Support (27 Languages) USB 2.0 (Micro 5 pin USB), HDMI (Type D)

Rechargeable Li-ion Battery LB-080, 3.6V 1250mAh, In-Camera Charging

Approx. 350 Shots (Based on CIPA Standards); Approx. 130 min. for Video (@1080p/30fps)

Temperature: 14° - 104°F / -10° - 40°C, Humidity: 0 - 90%

Approx. 3.33 x 2.02 x 1.55 in / 84.7 x 51.4 x 39.5 mm (Based on CIPA Standards)

Approx. 5.4 oz. / 155g (Body Only)

Rechargeable Li-ion Battery, AC Adapter, USB Cable, CD-ROM, Quick Start Guide, Warranty Card, Service Card,

Standard Lens Cover, Underwater Lens Cover

JK Imaging Ltd.

JK Imaging, Ltd. 1411 W. 190th Street, Suite 550 Gardena, CA 90248

To learn more about KODAK PIXPRO Digital Cameras: visit: www.kodakcamera.jkiltd.com











