Kodak PIXPRO

Digital Cameras

ASTRO ZOOM AZ522



FEATURES:

Memories are made for the taking with this sharp shooter. The KODAK PIXPRO AZ522 is the pinnacle of our Astro Zoom collection boasting a powerful 52x optical zoom, 9fps continuous shot and an electronic view finder for more options in capturing your priceless moments. With intuitive auto settings and a host of manual features, the AZ522 gives you every freedom to express your creativity and imagination. KODAK PIXPRO Digital Cameras. Tell your story.

- 52X Optical Zoom
- 24mm Wide Angle
- 16 MP CMOS
- 9 fps Burst Shooting
- Electronic View Finder
- OIS (Optical Image Stabilization)
- 3" LCD





























Digital Camera

SPECIFICATIONS AZ522

Effective Image Sensor Pixels Total Image Sensor Pixels

Lens

Focal Length [35mm film equivalent]

F number Lens Construction

Ontical Zoom Focusing Range

Anti-Handshake

Digital Zoom

Number of Recording Pixels Still Image

Movie

Image Compression DCF, DPOF (Ver1.1) Support

File Format

Still Image

Movie

Shooting Modes

Detection Features HDR Method

Photo Touch-up Panorama

LCD Display ISO Sensitivity

AF Method

Exposure Metering Method Exposure Control Method

Exposure Compensation Shutter Speed

Continuous Shooting Playback Modes

White Balance Control

Flash

Flash Method Flash Modes Shooting Range Recycling Time

Recording Media

Other Features Jacks

Power Shooting Capability

(Battery Performance) Operation Environment

Dimensions (WxHxD) Weight

Supplied Accessories

16.38 Megapixels

16.79 Megapixels [1/2.3" CMOS]

4.3 mm (Wide) — 223.6 mm (Tele) [24 mm (Wide) - 1248 mm (Tele)] F2.8 (Wide) - F5.6 (Tele) 13 groups 15 elements

52x

Normal: (Wide) 60 cm $-\infty$, (Tele) 300 cm $-\infty$

Macro: 1 cm - ∞ (Wide Only) Optical Image Stabilization

4x Digital Zoom (Combined Zoom: 208x)

(4:3) 16MP: 4608x3456, 10MP: 3648x2736, 5MP: 2592x1944, 3MP: 2048x1536, 0.3MP: 640x480, (3:2) 14MP: 4608x3072, (16:9) 12MP: 4608x2592, 2MP: 1920x1080

1920x1080: 30fps, 1280x720: 60fps / 30fps, 640x480: 30fps; High-Speed Movie 640x480: 120fps

Best, Fine, Normal

Yes

Exif 2.3 (JPEG)

Movie Format: MOV (H.264), Audio: Linear PCM [Stereo]

Auto, P, S, A, M, Face Beautifier, Panorama, Movie, CS, SCN [Children, Portrait, Night Portrait, Handheld Night, Landscape, Sport

Sunset, Fireworks, Multi Exposure, Snow, Party, Pet

Face, Smile, Blink, Cat, Dog

Red-Eye Removal, Skin Soften, Eye Brightening, Eye Enlargement

0° - 360° 3.0 inch (460K Pixels)

Auto, ISO 100/200/400/800/1600/3200

Single AF, Multi-AF (TTL 25-point), Object Tracking, Face Detection

Artificial Intelligence AE (AiAE), Center-Weighted Average, Spot (Fixed to Center of Frame), Face AE

Program AE (AE-Lock Available), Aperture Priority AE, Shutter Priority AE

+/- 3EV in 1/3 Step Increments

1/2000 - 30 Seconds Approx. 9 fps (Full Resolution)

Single Photo, Index (9/16 Thumbnails) Slide Show, Date, Burst Shooting, Zoom (Approx. x2 - x8) Auto (AWB), Daylight, Cloudy, Flourescent, Flourescent CWF, Incandescent, Manual, Color Temperature

Setting (1900K ~ 10000K)

Pop-up (Auto)

Auto, Red-Eye Reduction, Forced Flash, No Flash, Slow Synchro, Red-Eye Reduction + Slow Synchro

(Wide) Approx. 0.5 m - 7.5 m (ISO800); (Tele) Approx. 1.2 m - 3.7 m (ISO800)

6 seconds or less

Internal Memory: Approx. 8MB

SD/SDHC Card (Up to 32GB Support) [MMC Card not supported]

Eye-Fi, PictBridge, ExifPrint Support, Multi-Language Support (27 Languages)

AV-OUT/USB 2.0 (Micro 5 pin USB), HDMI (Type D) Rechargeable Li-ion Battery LB-060, 3.7V 1100mAh, In-Camera Charging

Approx. 240 Shots (Based on CIPA Standards)

Temperature: 32° - 104°F / 0° - 40°C, Humidity: 0 - 90%

Approx. 4.68 x 3.5 x 3.84 in. / 118.9 x 88.9 x 97.5 mm (Based on CIPA Standards)

Approx. 18.6 oz. / 530 g (Body Only)

Rechargeable Li-ion Battery, AC Adapter, USB Cable, Neck Strap, Lens Cap, CD-ROM, Service Card, Quick Start Guide, Warranty

JK Imaging Ltd.

JK Imaging, Ltd. 1411 W. 190th Street, Suite 550 Gardena, CA 90248

To learn more about KODAK PIXPRO Digital Cameras: visit: www.kodakcamera.jkiltd.com











