

Kodak

PIXPRO

Digital Cameras

ASTRO ZOOM AZ525



FEATURES:

Beauty is in the eye of the beholder with the KODAK PIXPRO AZ525 Astro Zoom Camera. Better than ever, all the power and performance you could wish for is harnessed in this cutting-edge, mega zoom bridge camera. Amazing detail, plenty of features and 52x optical zoom that gets you up close are just the beginning. Explore the power and freedom the AZ525 affords you first hand. KODAK PIXPRO Cameras - Tell your story.

- 52X Optical Zoom
- 24 mm Wide Angle
- 16 MP CMOS
- 6 fps Burst Shooting
- 3" LCD
- Wi-Fi Connection
- Wirelessly Control with your iOS/Android device



Available Colors: ●

52X
OPTICAL
ZOOM

24mm
WIDE

16MP
CMOS

1080p
FULL HD

WiFi
CERTIFIED

360°
Panorama

Kodak

PIXPRO AZ525

Digital Camera

52X
OPTICAL
ZOOM

24mm
WIDE

16MP
CMOS

1080p
FULL HD

WiFi
CERTIFIED

360°
Panorama

SPECIFICATIONS

AZ525

| | |
|--|---|
| Effective Image Sensor Pixels | 16.35 Megapixels |
| Total Image Sensor Pixels | 16.76 Megapixels [1/2.3" BSI CMOS] |
| Lens | |
| Focal Length [35mm film equivalent] | 4.3 mm (Wide) — 223.6 mm (Tele) [24 mm (Wide) — 1248 mm (Tele)] |
| F number | F2.8 (Wide) — F5.6 (Tele) |
| Lens Construction | 13 groups 15 elements |
| Compatible Filter Diameter | Ø52mm |
| Optical Zoom | 52x |
| Focusing Range | Normal: (Wide) 60 cm — ∞, (Tele) 300 cm — ∞ Macro: 1 cm — ∞ (Wide Only) |
| Anti-Handshake | OIS (Optical Image Stabilization) |
| Digital Zoom | 4x Digital Zoom (Combined Zoom: 208x) |
| Number of Recording Pixels | |
| Still Image | (4:3) 16MP: 4608x3456, 10MP: 3648x2736, 5MP: 2592x1944, 3MP: 2048x1536, 0.3MP: 640x480, (3:2) 14MP: 4608x3072, (16:9) 12MP: 4608x2592, 2MP: 1920x1080 |
| Movie | 1920x1080: 30fps, 1280x720: 60fps / 30fps, 640x480: 30fps; High-Speed Movie 640x480: 120fps |
| Image Compression | Best, Fine, Normal |
| DCF, DPOF (Ver1.1) Support | Yes |
| File Format | |
| Still Image | Exif 2.3 (JPEG) |
| Movie | Movie Format: MOV (H.264), Audio: Linear PCM [Stereo] |
| Shooting Modes | Auto, P, S, A, M, Face Beautifier, Wi-Fi, Movie, CS |
| SCN Modes | Children, Portrait, Night Portrait, Handheld Night, Landscape, Sport, Sunset, Fireworks, Multi Exposure, Snow, Party, Pet, Panorama |
| Detection Features | Face, Smile, Blink, Cat, Dog |
| HDR Method | Yes |
| Photo Touch-up | Red-Eye Removal, Skin Soften, Eye Brightening, Eye Enlargement |
| Panorama | 0° - 360° |
| LCD Display | 3.0 inch (460K Pixels) |
| ISO Sensitivity | Auto, ISO 100/200/400/800/1600/3200 |
| AF Method | Single AF, Multi-AF (TTL 25-point), Object Tracking, Face Detection |
| Exposure Metering Method | Artificial Intelligence AE (AiAE), Center-Weighted Average, Spot (Fixed to Center of Frame), Face AE |
| Exposure Control Method | Program AE (AE-Lock Available), Aperture Priority AE, Shutter Priority AE |
| Exposure Compensation | +/- 3EV in 1/3 Step Increments |
| Shutter Speed | 1/2000 - 30 Seconds |
| Continuous Shooting | Approx. 6 fps (Full Resolution) |
| Playback Modes | Single Photo, Index (9/16 Thumbnails) Slide Show, Date, Burst Shooting, Zoom (Approx. x2 - x8) |
| White Balance Control | Auto (AWB), Daylight, Cloudy, Flourescent, Flourescent CWF, Incandescent, Manual, Color Temperature Setting (1900K - 10000K) |
| Flash | |
| Flash Method | Pop-up (Manual) |
| Flash Modes | Auto, Red-Eye Reduction, Fill Flash, Slow Synchro, Red-Eye Reduction + Slow Synchro |
| Shooting Range | (Wide) Approx. 0.5 m - 7.5 m (ISO800); (Tele) Approx. 1.2 m - 3.7 m (ISO800) |
| Recycling Time | 6 seconds or less |
| Recording Media | Internal Memory: Approx. 8MB SD/SDHC Card (Up to 32GB Support) [MMC Card not supported] |
| Other Features | Wi-Fi (802.11 b/g/n), Remote Control (via iOS/Android Device), Eye-Fi, PictBridge, ExifPrint Support, Multi-Language Support (27 Languages) |
| Jacks | AV-OUT/USB 2.0 (Micro 5 pin USB), HDMI (Type D) |
| Power | Rechargeable Li-ion Battery LB-060, 3.7V 1100mAh, In-Camera Charging |
| Shooting Capability (Battery Performance) | Approx. 240 Shots (Based on CIPA Standards) |
| Operation Environment | Temperature: 32° - 104°F / 0° - 40°C, Humidity: 0 - 90% |
| Dimensions (WxHxD) | Approx. 4.78 x 3.38 x 3.84 in. / 121.3 x 85.8 x 97.5 mm (Based on CIPA Standards) |
| Weight | Approx. 17.9 oz. / 508 g (Body Only) |
| Supplied Accessories | Rechargeable Li-ion Battery, AC Adapter, USB Cable, Neck Strap, Lens Cap, Service Card, Quick Start Guide, Warranty Card |

JK Imaging Ltd.

JK Imaging Ltd.
17239 South Main Street
Gardena, CA 90248

To learn more about KODAK PIXPRO Digital Cameras:
visit: kodakpixpro.com

