

Kodak PIXPRO

Digital Devices

SL5 SMART LENS® CAMERA



FEATURES:

Your smart phone just got a whole lot better. Introducing the KODAK PIXPRO SL5 SMART LENS® camera. 5x mega zoom, built-in flash, and easy to attach to your smart phone for better looking photos and videos. And if that wasn't enough, the SL5 is wireless so you have even more flexibility to use it with or without your phone and upload your favorite shots to your social media streams. KODAK PIXPRO Digital Cameras - Tell your story.

- 16MP BSI CMOS sensor
- 5X Optical Zoom
- 28mm Wide Angle
- Full HD 1080p Video
- 6 fps Burst Shooting
- Wi-Fi / NFC Compatible
- Wirelessly Connect / Control with Smart iOS/Android Devices



Available Colors:  



16MP
CMOS



5X
OPTICAL
ZOOM



28mm
WIDE



1080p
FULL HD



WiFi
CERTIFIED



Lithium-ion
BATTERY


Kodak PIXPRO SL5

Digital Device



SPECIFICATIONS

SL5

Effective Image Sensor Pixels	16.35 Megapixels
Total Image Sensor Pixels	16.76 Megapixels [1/2.3" BSI CMOS]
Lens	
Focal Length [35mm film equivalent]	5.1 mm (Wide) — 25.5 mm (Tele) [28 mm (Wide) — 140 mm (Tele)]
F number	F3.9 (Wide) — F6.3 (Tele)
Lens Construction	8 groups 8 elements
Optical Zoom	5x
Focusing Range	Normal: (Wide) 60cm — ∞, (Tele) 100 cm — ∞ Macro: 5 cm — ∞ (Wide Only)
Autofocus System	TTL Autofocus
Number of Recording Pixels	
Still Image	(4:3) 16MP: 4608x3456, 10MP: 3648x2736, (16:9) 12MP: 4608x2592, 2MP: 1920x1080
Movie	1920x1080-30fps, 1280x720-30fps; High-Speed Movie: 848x480-120 fps
File Format	
Still Image	Exif 2.3 (JPEG)
Movie	MP4 [Image: H.264; Audio: AAC (Monaural)]
Shooting Modes	Movie, Photo
SCN Modes	P, ASCN, Burst Shooting, Low Light (WDR)
ISO Sensitivity	Auto, ISO 100/200/400/800/1600/3200
AF Method	Single AF, Touch
Exposure Metering Method	Artificial Intelligence AE (AiAE)
Exposure Control Method	Program AE (AE-Lock Available)
Exposure Compensation	+ 3EV in 1/3 Step Increments
Shutter	
Type	Mechanical Shutter and Electronic Shutter
Speed	1/2000 - 4 Seconds
Continuous Shooting	Approx. 6fps (Full Resolution)
White Balance Control	Auto (AWB), Daylight, Cloudy, Flourescent, Flourescent CWF, Incandescent
Flash	
Flash Method	Internal
Flash Modes	Auto, Fill Flash, Foreced Off
Shooting Range	(Wide) Approx. 0.3m - 2.5m (ISO800); (Tele) Approx. 0.5m - 1.5m (ISO800)
Recording Media	Micro SD/Micro SDHC Card (Class 4 Micro SD card or better, 32GB Max. Support) [MMC Card Not Supported]
Jacks	USB 2.0 (Micro 5 pin USB)
Wi-Fi	Yes (802.11 b/g/n)
NFC	Yes
Remote Control	Yes (via Smartphone)
Power	Rechargeable Li-ion Battery LB-012, 3.7V 700mAh, In-Camera Charging
Shooting Capability (Battery Performance)	Approx. 160 Shots (Based on CIPA Standards)
Operation Environment	Temperature: 32° - 104°F / 0° - 40°C, Humidity: 0 - 90%
Dimensions (WxHxD)	Approx. 2.15 x 2.15 x 1.68 in / 54.8 x 54.8 x 42.9 mm (Based on CIPA Standards)
Weight	Approx. 4.30 oz. / 122 g (Body Only)
Supplied Accessories	Rechargeable Li-ion Battery, AC Adapter, Wrist Strap, USB Cable, Quick Start Guide, Service Card, Warranty Card
Compatible Devices	 Your smart device operating system version needs to be iOS 7 or higher or Android 4.2 or higher. If not, please upgrade your smart device before installing or using the APP.

JK Imaging Ltd.

JK Imaging Ltd.
17239 South Main Street
Gardena, CA 90248

To learn more about KODAK PIXPRO Digital Cameras:
visit: kodakpixpro.com

